



This USB 2.0 USB-C to USB-B cable is the perfect solution for connecting a printer, hub, or other device that has a USB B port to a computer, tablet or other device that has a USB Type-C port for USB 2.0 communication. The color coded USB Type-C connector allows this cable to be easily identified as a USB 2.0 cable and differentiated from other cables which may support a different feature set. The USB Type-C connector is smaller than traditional USB connector and features a symmetrical design which allows it to be easily connected on the first try. Additionally, the durability of the USB Type-C connector allows for up to 10,000 connection cycles. This cable supports a data rate up to 480Mbps for data transfer and sync with 5 volts and 1 amp of power for device operation and charging. Note: This cable is designed to support USB 2.0 communication and features and is not able to support USB 3.1 Gen 2 Communication and features.

Learn more about the new [USB 3.1 Specification and new USB Type-C Connector](#).

Features & Benefits

Connect the USB-B port of a printer, hub or other device a USB Type-C port

Designed to support USB 2.0 communication and features

Backwards compatible with USB 2.0 and USB 1.1 devices

Color coded white and labeled to designate USB 2.0 feature support

Specifications

General Info

| | | | |
|--------------------|-------------------------|-------------------|----------|
| Product Line | C2G | Color | Black |
| UPC Number | 757120288602 | Country Of Origin | Vietnam |
| Application Sector | Commercial, Residential | Warranty Type | Lifetime |
| Type | Cable | | |

Dimensions

| | | | |
|-------------------|---------|--------------|-------|
| Product Length US | 10.0 FT | Cable Length | 10 ft |
|-------------------|---------|--------------|-------|

Listing Agencies / 3rd Party Agencies

| | | | |
|--------------|-----|---------------|-----|
| CE Certified | Yes | FCC Compliant | Yes |
|--------------|-----|---------------|-----|

Technical Information

| | | | |
|-----------------------|--------------------------|---------------------|---------------|
| Jacket Material | PVC (Polyvinyl Chloride) | Wire Gauge | 30 AWG |
| Storage Humidity | 0-90% RH | Bend Radius | 38 mm |
| Conductor Stranding | Stranded | Signal Transmission | Bidirectional |
| Cable Type | USB | Amperage | 1 A |
| Cable Diameter | 3.8 mm | Data Transfer Rate | 480 Mbps |
| Connector 2 | USB-B Male | Connector 1 | USB-C Male |
| Operating Temperature | 0°-50°C | Operating Humidity | 20-85% RH |
| Storage Temperature | -25° - 70° C | | |
